



Declaration of Performance

According to Annex III of Regulation (EU) No. 305/2011
 Nr. DoP – NoPB/0103/13/001
 for the product

Eurovent GEO TEC 250

1. Unique identification code of the product type:	Eurovent GEO TEC 250, nr NoPB/0104/13/001, accord. to. DIN EN 13252 : 2000 + A1:2005
2. Type batch or serial number or any other element allowing identification of the construction product as required und article 11(4)	Example + (lot nr. see packaging)
3. Intended use or uses of the construction product in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer	Geotextiles and geotextile-related products. Intendent uses: S + F + D
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required und article 11(2)	Eurosystem Polska Sp. z o.o. Wiejska 13, 46-055 Przywory, Polska VAT PL 9372516153
5. Contact address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in article 12 (2)	not relevant
6. AVCP: System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V	System 2+
7. Notified body: In case of declaration of performance concerning a construction product covered by a harmonised standard	1213-CPD-3697 Notified factory production control 1213 SKZ - TeConA GmbH, Würzburg performed the initial inspection of the manufacturing and of factory production control and issued the certificate of conformity of the production control 1213-CPD-3697

8. Declared performance

Essential characteristics	Performance		Harmonized technical specification
	Units	Values	
Tensile strength MD	[kN/m]	4,6	EN ISO 10319
Tensile strength CMD	[kN/m]	5,2	
Resistance to dynamic perforation	[mm]	45	EN ISO 13433
Characteristic opening size	O ₉₀ [μm]	175	EN ISO 12956
Water permeability	10 ⁻³ [m/s]	100	EN ISO 11058
Water flow capacity in the plane	[l/m ² s]	2,9	EN ISO 12958
Durability	1. To be covered 2 weeks after installation.		EN 12224
	2. Predicted to be durable in natural soils with 4<pH<9 and soil temperature <25 °C		EN ISO 13438

9. Declaration: the performance of the product is in conformity with the declared performance in point 9. This declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 4.

Przywory, 17.06.2013

Marcin Świerta
President

