


Eurovent FLEX EPDM

Self-adhesive pleated chimney flashing for use in sealing and finishing works around chimneys, bay windows and roof windows. Made of high-quality reinforcing grid, coated with EPDM and backed with butyl adhesive.



Advantages:

- flexible and easy to use
- resistance to water and cold
- UV resistance

Technical data:

Parameter	Value
Material	High-quality reinforcing grid, EPDM, butyl adhesive
EPDM	Thickness: 1,6 mm
Cover	2 perforated liners with easy application

Parameter	Value
Roll's width	300 mm
Roll's length	5 rm
Application temperature	from 5°C to 40°C
Available colors	wallred RAL 8004, brown RAL 8019, black RAL 9005
Packaging	2 roll in a box 96 rolls on a pallet

Application:

Pleated flashing tape for use in sealing and finishing works around chimneys, bay windows and roof windows. Product can also be applied for joining the roof with the wall. Suitable for application with cement and clay roof tiles as well as metal roofing.

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 01/2016

Eurovent **FLEX EPDM**

Montage:

Please ensure that the surface you want to apply the flashing on is clean and dry. Peel off the security liner, place the tape, and apply some pressure.

Safety

Try to avoid direct, long term skin butyl exposure. Before a break or finishing the application please wash your hands.

Storage / transport:

The tape should be stored in a dry place, under cover, free from moisture and UV radiation. The rolls are made partially from elastic aluminum- please store in original, closed boxes. Please protect from damages. Rolls should be transported in covered means of transport. They should be prepared for transport in a manner that protects them from damage and destruction. During transport safety regulations must be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of foil or permanently damage it.

The product is under warranty, providing that the guidelines contained in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 01/2016