


TECHNICAL DATA SHEET

Eurovent **FLEX STANDARD PB**

Self-adhesive chimney flashing tape for use in sealing and finishing works around chimneys, bay windows and roof windows. Suitable also for joining surfaces of roof and wall. Made of high-quality lead tape characterized by crosswise surface pattern, and butyl adhesive.



Advantages:

- flexible and easy to use
- resistance to water and cold
- UV resistance

Technical data:

Parameter	Value
Material	Lead, butyl tape
Lead	Width: 300 mm Thickness: 0,20 mm
Butyl tape	Size: 290 mm x 1,0 mm, Color: black with liner Thickness: $1,65 \pm 0,05 \text{ g/cm}^3$ Peel strength: $>25 (35 \pm 10) \text{ N/24 mm}$ Thinners: none used Resistance to aging: good, even in hot and humid conditions

Parameter	Value
Roll's width	300 mm
Roll's length	5 mb
Application temperature	from 5°C to 40°C
Available colors	wallred RAL 8004, brown RAL 8019, black RAL 9005, anthracite 7021
Packaging	1 roll in a box 60 rolls on a pallet

Application:

Flat flashing tape for use in sealing and finishing works around chimneys, bay windows and roof windows. Product can also be used for joining the roof with the wall. Suitable for application with cement and clay roof tiles as well as metal roofing.

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 01/2016

Eurovent **FLEX STANDARD PB**

Montage:

Please ensure that the surface you want to apply the butyl on is clean and dry. Peel off the security liner, place the tape, and apply some pressure.

Safety

Try to avoid direct, long term skin butyl exposure. Before a break or finishing the application please wash your hands.

Storage / transport:

The tape should be stored in a dry place, under cover, free from moisture and UV radiation. The rolls are made partially from elastic lead - please store in original, closed boxes. Please protect from damages. Rolls should be transported in covered means of transport. They should be prepared for transport in a manner that protects them from damage and destruction. During transport safety regulations must be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of foil or permanently damage it.

The product is under warranty, providing that the guidelines contained in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 01/2016