

Eurovent VALLEY Q

Roof valley made of crosswise pressed aluminum sheet and coated with polyester paint. Designed for use as flashing element between two neighbouring roof slopes. Ensures proper drainage of water from the roof.

Advantages:

- fast and easy installation
- weatherproof
- neat finishing



Technical data:

Parameter	Value
Material	Profiled aluminum sheet
Metal	Aluminium, thickness = 0,58 mm
Lakier	Polyester paint, covered with a protective film
Width	500 mm
Lenght	2000 mm
Available colours	wallred RAL 8004, brown RAL 8019, black RAL 9005, anthracite RAL 7021, chestnut RAL 8015, cherry RAL 3011, brown RAL 8017 (on request)
Package	10 pcs.
Pallet	40 cardboards = 400 pcs.

Application:

Roof valley designed for use as flashing element to ensure proper water drainage from the roof. Installed between the neighbouring roof slopes. Shape and dimensions enable fast and easy application. Suitable for use with majority of roof coverings available on the market.

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 11/2015

Eurovent VALLEY Q

Storage / transport:

The product should be stored in a dry place, under cover, free from moisture and UV radiation in original undamaged and closed package. Valleys are made of aluminum, which under the heavy weight may deform. We therefore, recommend not to stack valleys with other heavy products (both during transport and storage). The product should be transported in covered means of transport. They should be prepared for transport in a manner that protects them from damage and destruction. During transport safety regulations must be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of foil or permanently damage it.

The product is under warranty, providing that the guidelines contained in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 11/2015