

Eurovent VENTOS UNI EPDM

Universal ventilation chimney made from plastic and EPDM. It can be used for every type of embossing in roofing metal tiles, including the trapeze and standing-seam roof covering.

This chimney is an universal solution for most roof coverings apart from regular tiles. It's available with insulation on demand.

Advantages:

- quick and easy montage
- UV resistant
- large diameter



Technical data:

Parameter	Value
Material	Dyed polypropylene with added UV stabilizer + seal butyl
Roof angle for best application	10° - 45°
Base dimentions	44,4 x 33,8 cm
Available diameters	Ø 110 mm / Ø 150 mm
Available colors	Brown RAL 8017, black RAL 9005, graphite RAL 7024, chestnut RAL 3009, green RAL 6020, wallred RAL 8004, brown RAL 8019, anthracite RAL 7016, light grey RAL 7036

Parameter	Value
Available types of chimneys	Non-insulated / insulated (insulated with rubber foam)
UV Resistance	Resistant
Set	Chimney base + chimney + EPDM sealing + screws
UV Resistance	Resistant
Package weight	Aprox. 2 kg
Packaging	1 set
Pallet	36 chimneys

Application:

Ventilation chimney's main use is to ventilate, insulate and to release steam properly. It is used to ventilate humid air from the roof slope, ensuring proper air circulation and good roof ventilation. It can be used to ventilate attics, lofts, kitchens, bathrooms and sewage risers.

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 11/2015

Eurovent **VENTOS UNI EPDM**

Storage / transport:

The chimneys should be stored in closed, original boxes. Please protect from damage during storing. The product should be stored in a dry place, under cover, free from moisture and UV radiation in original undamaged and closed package. The product should be transported in covered means of transport. They should be prepared for transport in a manner that protects them from damage and destruction. During transport safety regulations must be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of foil or permanently damage it.

Additional information :

For fast and easy montage please use the attached in the box screws.

The product is under warranty, providing that the guidelines contained in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 11/2015