

Eurovent UNO

Single-sided tape made of polyethylene foil reinforced with polyester fibers and acrylic dispersion adhesive. Designed for sealing and repairing roof membranes, roof foils as well as other plastic-based construction materials. Adhesive surface is protected with silicone film.



Advantages:

- high adhesive strength
- solvent-free
- polyester mesh

Technical data:

Parameter	Value
Material	Polyethylene, polyester mesh, acrylic adhesive
Width	50 mm
Length	25 mb
Thickness	0,30 -0,33 mm
Grammage of glue	190 g/m ²
Peel adhesion	≥40 N/25 mm
Elongation	≥25 N/25 mm; 100%
Processing temperature	From -10°C. Recommended +5°C
Temperature resistance	-40°C do +80°C
Tack	Excellent
Condensation water resistance	Very high
Aging resistance	Very high
UV resistance	Resistant
Packaging	box – 12 rolls, 60 boxes on a pallet – 720 rolls
Storage	In dry spaces, in original packaging

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 01/2016

Eurovent UNO

Application:

Tape is designed for fixing and joining plastics with products based on polypropylene and polyethylene, paper-reinforced materials, wood, metal elements, plasterboards or stone. Effectively seals curved surfaces. Recommended for repairing all kinds of damages such as holes, cuts and installation punctures.

Storage / transport:

The product should be stored in a dry place, under cover, free from moisture and UV radiation in original undamaged and closed package. Rolls should be transported in covered means of transport. They should be prepared for transport in a manner that protects them from damage and destruction. During transport safety regulations must be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of foil or permanently damage it.

The product is under warranty, providing that the guidelines contained in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 01/2016